

# NSK 90BER10S angular contact ball bearings

How do I place an EMERGENCY 174.625 mm da order for a NSK 90BER10S angular contact ball bearings that 339.999 mm Da I want to pick up at a our store?

da	174.625 mm
Da	339.999 mm
Ca	101.803 mm
A1	190.5 mm
A2	273.05 mm
S	4.763 mm
ba	78.581 mm
H	401.637 mm
H1	200.025 mm
H2	79.375 mm
J min.	549.275 mm
J max.	619.125 mm
J1	114.3 mm
L	711.2 mm
N1	34.925 mm
R1	120.65 mm
R2	42.069 mm
RG	1 NPT
PG	1/4 NPT
h	61.913 mm
Housing	SAF 538
Bearing	22238 CCK/W33

Adapter sleeve assembly	SNW 38×6.7/8
Stabilizing ring	SR-38-32
Labyrinth ring	2 x LOR 154
PosiTrac Plus contact element	2 x B10724-155
End plug (suffix Y)	EPR 21
Max. speed for PosiTrac Plus seal	825 r/min
P60°	290 kN
P90°	173 kN
P120°	107 kN
P150°	94.3 kN
P180°	113 kN
Pa	52.5 kN
Mass pillow block	170 kg
Cap bolt	4 x 7/8-9 UNC
Cap bolt recommended tightening torque	271.2 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.25 in
Initial grease fill	1672.65 g