

NSK 93825A/93126 cylindrical roller bearings

Welcome to 50 mm da the 60.325 mm db NSK 93825A/93126 cylindrical roller bearings online seller.

da	50 mm
db	60.325 mm
dc	47.625 mm
Da	110 mm
Ca	50.8 mm
A1	69.85 mm
A2	190.5 mm
S	5.556 mm
ba	34.925 mm
H	147.637 mm
H1	76.2 mm
H2	28.575 mm
J min.	196.85 mm
J max.	228.6 mm
L	269.875 mm
N1	19.05 mm
R1	42.862 mm
R2	19.05 mm
RG	1/8 NPT
PG	1/8 NPT
h	34.925 mm
Housing	SAF 310
Bearing	22310 E

Lock nut	N 10
Lock washer	W 10
Stabilizing ring	SR-0-10
Taconite seal (db shaft position)	TER 35
Taconite seal (dc shaft position)	TER 23
End plug (suffix Y)	EPR 5
Max. speed for Taconite seal	1300 r/min
P60°	39.1 kN
P90°	23.6 kN
P120°	14.2 kN
P150°	12.9 kN
P180°	15.6 kN
Pa	9.79 kN
Mass pillow block	10.2 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	53.865 g