

NSK AR110-39 tapered roller bearings

Find the discount NSK AR110-39 tapered roller bearings 0.0 Inventory online you need . We offer ... If you check out our large selection of NSK AR110-39 tapered roller bearings once .

| | |
|-------------------------|------------------------------------------------------------------------------------------------------|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0.03 |
| EAN | 7316577002495 |
| Product Group | B04286 |
| Stud Profile | Male |
| Mounting Thread | M8 X 1.25 |
| Thread Direction | Right Hand |
| Rolling Element | Spherical Plain |
| Material – Outer Member | Steel |
| Material – Ball | Steel |
| Material – Liner | Teflon Sintered Bronze |
| Relubricatable | No |
| Enclosure | Open |
| Other Features | 3 Piece Zinc Plated Outer Self Lubricating Maintenance Free |
| Long Description | 8MM Bore; 6.5MM House Width; Male Stud Profile; M8 X 1.25; Right Hand Thread Direction; Spherical Pl |
| Inch – Metric | Metric |

| | |
|------------------------------|-----------------------------------|
| UNSPSC | 31171508 |
| Harmonized Tariff Code | 8483.30.80.55 |
| Noun | Bearing |
| Keyword 3 | Rod End |
| Keyword String | Plain Spherical Rod End |
| Manufacturer Item Number | SA 8 C |
| Weight / LBS | 0.066 |
| d | 8 mm |
| Housing Width | 0.256 Inch 6.5 Millimeter |
| Ball Width | 0.315 Inch 8 Millimeter |
| bore diameter: | 8 mm |
| ball material: | Steel |
| misalignment angle: | 15 ° |
| race material: | Bronze |
| shank thread length: | 21 mm |
| radial static load capacity: | 12.9 kN |
| rod end type: | Male Threaded |
| operating temperature range: | -50 to +150 °F |
| shank thread size: | M8 |
| head diameter: | 25 mm |
| thread direction: | Right Hand |
| head width: | 6.5 mm |
| grade: | Commercial/Industrial |
| ball width: | 8 mm |
| lubrication type: | Maintenance Free/Self-Lubricating |
| length to ball center: | 42 mm |
| housing material: | Zinc-Plated Steel |

| | |
|--------------------------------|----------------------------------|
| standards met: | ISO 12240-4:1998, ISO 965-1:1998 |
| d2 max. | 25 mm |
| B | 8 mm |
| G | M 8 |
| C1 max. | 6.5 mm |
| h | 42 mm |
| α | 15 ° |
| dk | 13 mm |
| l1 min. | 21 mm |
| l2 max. | 56 mm |
| l7 min. | 11 mm |
| r1 min. | 0.3 mm |
| Basic dynamic load rating C | 5.85 kN |
| Basic static load rating C0 | 12.9 kN |
| Specific dynamic load factor K | 100 N/mm ² |
| Material constant KM | 1400 |
| Mass rod end | 0.03 kg |