

# NSK B250-8 deep groove ball bearings

NSK B250-8 deep groove ball bearings Product Brochures N/A  
Minimum Buy Quantity , ASAHI BEARINGS Manufacturer Name 0.0  
Inventory Manufacturing Service . Get Your Free.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | ASAHI BEARINGS   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 5.906  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | UC212-36   |
| Seals                     | Contact Seal   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Single Row   Spherical   Normal Duty   Open Cover   Has Slinger                            |
| Long Description          | 2 Bolt Pillow Block; 2-1/4" Bore; 2-3/4" Base to Center Height; Set Screw Mount; Ball Bear |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.40                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | UCP212-36C                     |
| Weight / LBS                  | 10.36                          |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| D                             | 2.563 Inch   65.09 Millimeter  |
| Nominal Bolt Center to Center | 7.3 Inch   184 Millimeter      |
| d                             | 2.25 Inch   57.15 Millimeter   |
| Bolt Spacing Maximum          | 7.625 Inch   193.675Millimeter |
| B                             | 2.75 Inch   69.85 Millimeter   |
| Bolt Spacing Minimum          | 6.875 Inch   174.625Millimeter |