

# NSK B8-85 deep groove ball bearings

Welcome to the NSK B8-85 deep groove ball bearings 0.0 Inventory NSK Manufacturer Name online seller.

Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight	140
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Bronze
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AH2356 (Specify bore)
Inch – Metric	Metric
Long Description	280MM Tapered Bore; 500MM Outside Diameter; 176MM Width; C0-Medium Clearance; Adapter Mount; Double
Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available
UNSPSC	31171510
Harmonized Tariff Code	84823080

Noun	Bearing
Keyword String	Spherical
Manufacturer Item Number	23256CAMKE4
Weight / LBS	140
Adapter Part Number	SNP3256 (Specify bore) Inch   H2356 (Specify bore) Millimeter
D	19.685 Inch   500 Millimeter
d	280
B	6.929 Inch   176 Millimeter
bore diameter:	280 mm
maximum rpm:	670 RPM
outside diameter:	500 mm
operating temperature range:	Maximum of +200 °C
overall width:	176 mm
cage material:	Brass
bore type:	Tapered 1:12
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C0
precision rating:	RBEC 5 (ISO Class 5)
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	176 mm
dynamic load capacity:	2880000 N
fillet radius:	5 mm
static load capacity:	4900000 N
series:	232

Y3	1.9
hidYobi	23256CAMKE4
LangID	1
Y1	1.9
D_	500
Y2	2.9
Macha rpm	1300
C	3600
B_	176
da min	302
hidTable	ecat_NSSPHR
Oil rpm	670
da max	0
Y0	1.9
mass	147
GRS rpm	530
ra	4
TSR rpm	750
C0	4900
DE_	445.96
X0	1
Prod_Type3	SRB_CTB_TB
X1	1
X2	0.67
SIR	70
e	0.35
DA_	55
bomp	23256CAMKE4
Z_	18

ALP2	10
ALP1	13
ALP3	0
D_a max	478
D_a min	425
yobi	23256CAMKE4
HPS	HPS
ALPHA_	0.23
SDM_	392.406
r	5
SBRG	32
DI_	338.852