

NSK EE291201/291749 cylindrical roller bearings

NSK EE291201/291749 cylindrical roller bearings 131.762 mm da 269.999 mm Da Industries and Applications ? We sell discount online as well as cheap machinery parts.

| | |
|---------|---------------|
| da | 131.762 mm |
| Da | 269.999 mm |
| Ca | 105.816 mm |
| A1 | 158.75 mm |
| A2 | 215.9 mm |
| S | 4.763 mm |
| ba | 77.787 mm |
| H | 317.5 mm |
| H1 | 160.35 mm |
| H2 | 63.5 mm |
| J min. | 431.8 mm |
| J max. | 463.55 mm |
| J1 | 95.25 mm |
| L | 539.75 mm |
| N1 | 28.575 mm |
| R1 | 95.25 mm |
| R2 | 39.688 mm |
| RG | 3/8 NPT |
| PG | 1/4 NPT |
| h | 50.8 mm |
| Housing | SAW 530 |
| Bearing | 23230 CCK/W33 |

| | |
|--|----------------|
| Adapter sleeve assembly | SNW 130×5.3/16 |
| Stabilizing ring | SR-30-0 |
| Labyrinth ring | 2 x LOR 125 |
| End plug (suffix Y) | EPR 16 |
| Bearing limiting speed | 2200 r/min |
| P60° | 230 kN |
| P90° | 138 kN |
| P120° | 87.2 kN |
| P150° | 80.1 kN |
| P180° | 96.1 kN |
| Pa | 43.2 kN |
| Mass pillow block | 92.5 kg |
| Cap bolt | 4 x 3/4-10 UNC |
| Cap bolt recommended tightening torque | 359.3 N·m |
| Cap bolt, SAE grade | 5 |
| Eye bolt | 2 x 3/8-16 UNC |
| Appropriate attachment bolt size G | 1 in |
| Initial grease fill | 623.7 g |