

NSK F626DD deep groove ball bearings

NSK F626DD deep groove ball bearings 30 Outer Diameter (mm) manufacturer 78x30x49 Size (mm) and global supplier of reliable ball and roller ... NSK F626DD deep groove ball bearings Industries Products Manufacturing & Engineering and Agricultural Bearings designed to meet the unique requirements of our targeted industries.

| | |
|-------------------------------|------------|
| Size (mm) | 78x30x49 |
| Bore Diameter (mm) | 78 |
| Outer Diameter (mm) | 30 |
| Width (mm) | 49 |
| d | 30 mm |
| D | 78 mm |
| H | 49 mm |
| D1 | 40 mm |
| B | 12 mm |
| r1,2 – min. | 1 mm |
| r3,4 – min. | 0.6 mm |
| da | 40 mm |
| Da – max. | 55 mm |
| ra – max. | 1 mm |
| rb – max. | 0.6 mm |
| Basic dynamic load rating – C | 61.8 kN |
| Basic static load rating – C0 | 122 kN |
| Fatigue load limit – Pu | 4.5 kN |
| Reference speed | 2200 r/min |
| Limiting speed | 3000 r/min |

| | |
|----------------------------|--|
| Minimum load factor – A | 0.077 |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 1.036 |
| EAN | 7316577121301 |
| Product Group | B00308 |
| Rolling Element | Ball Bearing |
| Thrust Bearing | Yes |
| Single or Double Direction | Double Direction |
| Banded | No |
| Cage Material | Steel |
| Precision Class | ABEC 1 ISO P0 |
| Component Description | Roller Assembly Plus Raceways |
| Other Features | Double Row |
| Long Description | 30MM Bore 1; 42MM Bore 2; 78MM Outside Diameter; 49MM Height; Ball Bearing; Double Direction; Not Ba |
| Inch – Metric | Metric |
| UNSPSC | 31171507 |
| Harmonized Tariff Code | 8482.10.50.08 |
| Noun | Bearing |
| Keyword String | Ball Thrust |
| Manufacturer Item Number | 52308 |
| Weight / LBS | 2.281 |
| Outside Diameter | 3.071 Inch 78 Millimeter |
| Bore 2 | 1.654 Inch 42 Millimeter |
| Bore 1 | 1.181 Inch 30 Millimeter |

| | |
|---|----------------------------|
| Overall Height with Aligning Washer | 0 Inch 0 Millimeter |
| Height | 1.929 Inch 49 Millimeter |
| bore diameter: | 30 mm |
| static load capacity: | 122 kN |
| outside diameter: | 78 mm |
| dynamic load capacity: | 61.8 kN |
| overall width: | 49 mm |
| maximum rpm: | 3000 RPM |
| thrust bearing type: | Double-Direction |
| cage material: | Steel |
| outside diameter design: | Straight |
| fillet radius: | 0.6 mm |
| separable or banded: | Separable |
| series: | 523 |
| precision rating: | ABEC 1 (ISO Class Normal) |
| D1 ≈ | 40 mm |
| r1,2 min. | 1 mm |
| r3,4 min. | 0.6 mm |
| Da max. | 55 mm |
| ra max. | 1 mm |
| rb max. | 0.6 mm |
| Basic dynamic load rating C | 61.8 kN |
| Basic static load rating C0 | 122 kN |
| Fatigue load limit Pu | 4.5 kN |
| Minimum load factor A | 0.077 |
| Mass bearing (including seat washer where applicable) | 1.05 kg |