

# NSK FNTA-90120 needle roller bearings

NSK FNTA-90120 needle roller bearings, Units and Housings CAD 0.0 Inventory models , Manufacturing Service . Get N/A Minimum Buy Quantity Your Free.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 10.96   |
| EAN                       | 0013992043962   |
| Product Group             | B04144  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Clamp Collar  |
| Housing Style             | 4 Bolt Round Flange Block   |
| Rolling Element           | Cylindrical Roller Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-Expansion   |
| Mounting Bolts            | 12 Millimeter   |
| Relubricatable            | Yes   |
| Insert Part Number        | LSM65BR   |
| Seals                     | Triple Lip Labyrinth  |
| Housing Configuration     | 2 Piece Split   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Metric  |
| Long Description          | 4 Bolt Round Flange Block;<br>65MM Bore; 218MM Bolt Circle;<br>2 Piece Split; Clamp Collar<br>Mount; Cast Iro |

|                                    |   |
|------------------------------------|---|
| Other Features                     | Single Row   Wide Inner Ring   Light Duty |
| UNSPSC                             | 31171501                                  |
| Harmonized Tariff Code             | 8483.20.40.80                             |
| Noun                               | Bearing                                   |
| Keyword String                     | Flanged                                   |
| Weight / LBS                       | 24.15                                     |
| d                                  | 2.559 Inch   65 Millimeter                |
| Nominal Bolt Circle Diameter Round | 8.6 Inch   218 Millimeter                 |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter                     |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter                     |
| Bolt Spacing                       | 6.1 Inch   154.9 Millimeter               |
| D                                  | 2.362 Inch   60 Millimeter                |