

NSK FWF-475230 needle roller bearings

Welcome to the 147.637 mm da 359.999 mm Da NSK FWF-475230 needle roller bearings online 129.794 mm Ca seller.

da	147.637 mm
Da	359.999 mm
Ca	129.794 mm
A1	203.2 mm
A2	285.75 mm
S	4.763 mm
ba	91.281 mm
H	422.275 mm
H1	209.55 mm
H2	85.725 mm
J min.	571.5 mm
J max.	635 mm
J1	127 mm
L	749.3 mm
N1	34.925 mm
R1	122.237 mm
R2	42.862 mm
RG	1 NPT
PG	1/4 NPT
h	69.85 mm
Housing	SAF 634
Bearing	22334 CCK/W33
Adapter sleeve assembly	SNW 134×5.13/16

Stabilizing ring	SR-40-34
Labyrinth ring	2 x LOR 138
PosiTrac Plus contact element	2 x B10724-140
End plug (suffix Y)	EPR 18
Max. speed for PosiTrac Plus seal	950 r/min
P60°	364 kN
P90°	218 kN
P120°	136 kN
P150°	120 kN
P180°	145 kN
Pa	60.9 kN
Mass pillow block	213 kg
Cap bolt	4 x 7/8-9 UNC
Cap bolt recommended tightening torque	271.2 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.25 in
Initial grease fill	2154.6 g