

NSK H936340/H936316 cylindrical roller bearings

Browse NSK H936340/H936316 cylindrical roller bearings 75 Bore Diameter (mm) Categories in 75x160x37 Size (mm) 160 Outer Diameter (mm) the Manufacturers Online Free. including .

Size (mm)	75x160x37
Bore Diameter (mm)	75
Outer Diameter (mm)	160
Width (mm)	37
d	75 mm
D	160 mm
B	37 mm
C	37 mm
r min.	2,1 mm
da min.	86 mm
da max	99 mm
Da max.	149 mm
ra max.	2 mm
Weight	3,02 Kg
Basic dynamic load rating (C)	113 kN
Basic static load rating (C0)	77 kN
Reference speed	2 900 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	3.054
EAN	4547359005837

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	75MM Bore; 160MM Outside Diameter; 37MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Alvania Prelubricat
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	6.66
Bore	2.953 Inch 75 Millimeter
Outer Race Width	1.457 Inch 37 Millimeter
Outside Diameter	6.299 Inch 160 Millimeter
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	75 mm
static load capacity:	77000 N

outside diameter:	160 mm
precision rating:	ISO Class 0
overall width:	37 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	37 mm
snap ring included:	Without Snap Ring
outer ring width:	37 mm
internal clearance:	CN
maximum rpm (grease):	2900 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	2.1 mm
dynamic load capacity:	113000 N
manufacturer product page:	Click here