

# NSK HJ-14017048 + IR-12014048 needle roller bearings

Enjoy 0.0 Inventory High Margins on Competitive Pricing.Great Wholesale Products at Low SKF Manufacturer Name Costs.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.06
EAN	7316570368260
Product Group	B04286
Stud Profile	Male
Mounting Thread	M10 X 1.5
Thread Direction	Left Hand
Rolling Element	Spherical Plain
Material – Outer Member	Steel
Material – Ball	Steel
Material – Liner	Plastic   Teflon
Relubricatable	No
Enclosure	Open
Other Features	2 Piece   Zinc Plated Outer   Self Lubricating   Maintenance Free
Long Description	10MM Bore; 10.5MM House Width; Male Stud Profile; M10 X 1.5; Left Hand Thread Direction; Spherical P
Inch – Metric	Metric
UNSPSC	31171508

Harmonized Tariff Code	8483.30.80.55
Noun	Bearing
Keyword 3	Rod End
Keyword String	Plain Spherical Rod End
Manufacturer Item Number	SALKB 10 F
Weight / LBS	0.13
d	10 mm
Ball Width	0.551 Inch   14 Millimeter
Housing Width	0.413 Inch   10.5 Millimeter
bore diameter:	10 mm
ball material:	Steel
misalignment angle:	13 °
race material:	PTFE Composite
shank thread length:	28 mm
radial static load capacity:	12.5 kN
rod end type:	Male Threaded
operating temperature range:	-40 to +75 °F
shank thread size:	M10
head diameter:	29 mm
thread direction:	Left Hand
head width:	10.5 mm
grade:	Commercial/Industrial
ball width:	14 mm
lubrication type:	Maintenance Free/Self-Lubricating
length to ball center:	48 mm
housing material:	Zinc-Plated Steel
standards met:	ISO 12240-4:1998, ISO 965-1:1998

d2 max.	29 mm
B	14 mm
G	M 10
C1 max.	11.5 mm
h	48 mm
$\alpha$	13 °
dk	19 mm
l1 min.	28 mm
l2 max.	64 mm
r1 min.	0.3 mm
Basic dynamic load rating C	9.8 kN
Basic static load rating C0	12.5 kN
Specific dynamic load factor K	50 N/mm <sup>2</sup>
Material constant KM	530
Mass rod end	0.059 kg