

NSK HR30236J tapered roller bearings

The online NSK HR30236J tapered roller bearings 160 Bore Diameter (mm) parts store gives you immediate access to a selection of more than 160x240x60 Size (mm) 1.4 million new, used, remanufactured.

Size (mm)	160x240x60
Bore Diameter (mm)	160
Outer Diameter (mm)	240
Width (mm)	60
d	160 mm
D	240 mm
B	60 mm
C	60 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	9.09
EAN	4547359132540
Product Group	B04270
Bore Profile	Tapered
Cage Material	Brass
Precision Class	ABEC 7 ISO P4
Number of Rows of Rollers	Double Row
Separable	Outer Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing

Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C1NA
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	3 Rib Inner Ring Plain Outer Ring Precision Bearing Cage on Inner Ring OD
Long Description	160MM Bore; Tapered Bore Profile; 240MM Outside Diameter; 60MM Width; Brass Cage Material; ABEC 7
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NN3032KC1NAP4
Weight / LBS	20.023
Outside Diameter	9.449 Inch 240 Millimeter
Bore	6.299 Inch 160 Millimeter
Width	2.362 Inch 60 Millimeter
bore diameter:	160 mm
maximum rpm:	2900 rpm
outside diameter:	240 mm
bearing material:	Hardened Alloy Steel
overall width:	60 mm
cage material:	High Strength, 2 piece, Machined Brass
flanges:	(3) Inner Ring

finish/coating:	Uncoated
bore type:	Tapered 1:12
closure type:	Open
number of rows:	2
resistance features:	Clean Room, Vacuum
internal clearance:	C1NA
outer ring width:	60 mm
operating temperature range:	-40 to 120 °C
fillet radius:	2.1 mm
dynamic load capacity:	375000 N
series:	NN30K
static load capacity:	660000 N
manufacturer product page:	Click here
precision rating:	ISO Class 4