NSK HR30312DJ tapered roller bearings

Our 0.0 Inventory highly-skilled and factory-trained service experts have the resources to help you with all your NSK HR30312DJ tapered roller bearings needs — including routine maintenance, NTN Manufacturer Name major repairs, warranty service, and equipment inspections.

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	5.566
EAN	4547359309898
Product Group	B00152
Enclosure	0pen
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1 ISO PO
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	25 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch — Metric	Metric

Long Description	75MM Bore; 160MM Outside Diameter; 68.3MM Width; Open; No Flush Ground; Ball Bearing; Double Row of
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	5315
d	2.953 Inch 75 Millimeter
В	2.689 Inch 68.3 Millimeter
D	6.299 Inch 160 Millimeter
bore diameter:	75 mm
radial static load capacity:	145000 N
outside diameter:	160 mm
operating temperature range:	-40 to 120 ºC
overall width:	2.7500 in
cage material:	Steel
contact angle:	25 °
outer ring width:	68.3 mm
row type & fill slot:	Double-Row Non-Fill Slot
maximum rpm:	3200 RPM
internal clearance:	C0
finish/coating:	Uncoated
bore type:	Round
precision rating:	Class 0
closure type:	0pen
fillet radius:	2.1 mm
snap ring included:	Without Snap Ring
series:	53

bearing material:	High Carbon Chrome Steel
weight:	5.561 kg
radial dynamic load capacity:	173000 N
manufacturer product page:	Click here