

# NSK HR30321J tapered roller bearings

How do you find the NSK HR30321J tapered roller bearings specification? Manufacturers 45 mm d 19 mm B Online Free check  85 mm D

d	45 mm
D	85 mm
B	19 mm
C	16 mm
T	20.75 mm
d1	64 mm
a	18 mm
rs min	1.5 mm
r1s min	1.5 mm
e	0.4
Y2	1.48
Y0	0.81
Mass	0.5 kg
ISO 355 reference	T3DB045
Dynamic load, C	67.5 kN
Rating life coefficient, A2	1
Static load, C0	78.5 kN
Fatigue limit load, Cu	9.6 kN
Nlim (oil)	5,900 rpm
Nlim (grease)	4,400 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C

Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.36 Hz
Characteristic outer ring frequency, BPF0	7.66 Hz
Characteristic inner ring frequency, BRFI	10.34 Hz
da max	54 mm
db min	53.5 mm
Da min	74 mm
Da max	76.5 mm
Db min	80 mm
Ca min	3 mm
Cb min	4.5 mm
ra max	1.5 mm
r1a max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.495
EAN	4547359291728
Product Group	B04334