

NSK HR32026XJ tapered roller bearings

NSK HR32026XJ tapered roller bearings manufacturer and 0.0 Inventory global supplier of reliable ball and roller ... NSK HR32026XJ tapered roller bearings N/A Minimum Buy Quantity Industries Products Manufacturing & Engineering and Agricultural Bearings designed to meet the unique requirements of our targeted industries.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	42.61
EAN	0013992059451
Product Group	B04144
Number of Mounting Holes	2
Mounting Method	Clamp Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Cylindrical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-Expansion
Mounting Bolts	24 Millimeter
Relubricatable	Yes
Insert Part Number	LSM115BR
Seals	Triple Lip Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Metric
Other Features	Single Row Light Duty With Support Wide Inner Ring

UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Weight / LBS	93.85
Actual Bolt Center to Center	15.4 Inch 392Millimeter
Bolt Spacing Minimum	0 Inch 0Millimeter
d	4.528 Inch 115 Millimeter
Nominal Bolt Center to Center	15.4 Inch 392 Millimeter
D	3.543 Inch 90 Millimeter
B	5.63 Inch 143 Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
Shaft Size	115 mm
Seal Type	Aluminium Triple Labyrinth
Bearing Type	Split Cylindrical Retained Type
Support Type	Two-Bolt Plummer Block
Series Type	Light Series
Pillow/Plummer Block Style	Split Cylindrical Housed Unit – Angled
Bolt Size	2 x M24
Dimension H	150 mm
Dimension H2	310 mm
Dimension J	380 mm
Dimension L	445 mm
Dimension M	130 mm
Housing Width	5.6 in
Cr – Dynamic Load Rating	71040 lbf
Cor – Static Load Rating	95993 lbf
Ca – Axial Load Rating	4181.39 lbf

Maximum Speed	1970 rpm
Note	This product line was formerly known as "Revolvo"