

# NSK LM1817 needle roller bearings

How do you find the NSK LM1817 needle roller bearings 90 Outer Diameter (mm) specification? 70 Bore Diameter (mm) Manufacturers 70x90x10 Size (mm) Online Free check

Size (mm)	70x90x10
Bore Diameter (mm)	70
Outer Diameter (mm)	90
Width (mm)	10
d	70 mm
D	90 mm
B	10 mm
C	10 mm
r min.	0,6 mm
da min.	74 mm
da max	75,5 mm
Da max.	86 mm
ra max.	0,6 mm
Weight	0,137 Kg
Basic dynamic load rating (C)	12,1 kN
Basic static load rating (C0)	11,9 kN
Reference speed	3 800 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.133
EAN	4547359586046

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	70MM Bore; 90MM Outside Diameter; 10MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0;
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6814LLU/2AS
Weight / LBS	0.294
Outside Diameter	3.543 Inch   90 Millimeter
Bore	2.756 Inch   70 Millimeter
Outer Race Width	0.394 Inch   10 Millimeter
Other Features	Deep Groove   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Shell Alvania Prelubricat
Inner Race Width	0 Inch   0 Millimeter
bore diameter:	70 mm

precision rating:	ISO Class 0
outside diameter:	90 mm
finish/coating:	Uncoated
overall width:	10 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	10 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	10 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	3800 rpm
internal clearance:	CN
fillet radius:	0.6 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	4100 RPM
dynamic load capacity:	12100 N
series:	68
static load capacity:	11900 N
manufacturer product page:	<a href="#">Click here</a>