

NSK LM1916 needle roller bearings

How do I place an EMERGENCY order for a NSK LM1916 needle roller bearings that 100x70x16 Size (mm) I want to pick up at a our store?

Size (mm)	100x70x16
Bore Diameter (mm)	100
Outer Diameter (mm)	70
Width (mm)	16
d	70 mm
D	100 mm
B	16 mm
d1	79.3 mm
d2	76.8 mm
D2	93.6 mm
r1,2 – min.	1 mm
r3,4 – min.	0.3 mm
a	20 mm
da – min.	74.6 mm
da – max.	78.7 mm
db – min.	72 mm
db – max.	76.2 mm
Da – max.	95.4 mm
Db – max.	98 mm
ra – max.	1 mm
rb – max.	0.3 mm
Basic dynamic load rating – C	22.1 kN

Basic static load rating – C0	16.3 kN
Fatigue load limit – Pu	0.68 kN
Limiting speed for grease lubrication	22000 r/min
Ball – Dw	9.525 mm
Ball – z	22
Calculation factor – f0	8.4
Preload class A – GA	120 N
Preload class B – GB	360 N
Preload class C – GC	710 N
Calculation factor – f	1
Calculation factor – f2A	1
Calculation factor – f2B	1.05
Calculation factor – f2C	1.09
Calculation factor – fHC	1.01
Preload class A	58 N/micron
Preload class B	92 N/micron
Preload class C	125 N/micron
r1,2 min.	1 mm
r3,4 min.	0.3 mm
da min.	74.6 mm
da max.	78.7 mm
db min.	72 mm
db max.	76.2 mm
Da max.	95.4 mm
Db max.	98 mm
ra max.	1 mm
rb max.	0.3 mm
Basic dynamic load rating C	22.1 kN
Basic static load rating C0	16.3 kN

Fatigue load limit P_u	0.68 kN
Attainable speed for grease lubrication	22000 r/min
Ball diameter D_w	9.525 mm
Number of balls z	22
Preload class A GA	120 N
Static axial stiffness, preload class A	58 N/ μ m
Preload class B GB	360 N
Static axial stiffness, preload class B	92 N/ μ m
Preload class C GC	710 N
Static axial stiffness, preload class C	125 N/ μ m
Calculation factor f	1.14
Calculation factor f_1	1
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.05
Calculation factor f_{2C}	1.09
Calculation factor f_{HC}	1.01
Calculation factor f_0	8.4
Mass bearing	0.28 kg