

NSK MR 137 deep groove ball bearings

NSK MR 137 deep groove ball bearings with easy-to-use parts graphics, giving you the ability to check parts availability, pricing, examine remanufactured options.

d	90 mm
D	160 mm
B	30 mm
E	143 mm
F	107 mm
d1	114.2 mm
rs min	2 mm
r1s min	2 mm
Radial clearance class	CN
Mass (without HJ ring)	2.5 kg
Dynamic load, C	152 kN
Static load, C0	178 kN
Fatigue limit load, Cu	20.3 kN
Nlim (oil)	5,000 rpm
Nlim (grease)	4,300 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.8 Hz
Characteristic outer ring frequency, BPF0	6.85 Hz

Characteristic inner ring frequency, BPF1	9.15 Hz
da min	99 mm
da max	105 mm
dc min	116 mm
Da max	151 mm
ra max	2 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	2.51
EAN	4547359118414
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – One Side
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	1 Rib Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID

Long Description	90MM Bore; Straight Bore Profile; 160MM Outside Diameter; 30MM Width; Brass Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NJ218G1
Weight / LBS	5.529
Width	1.181 Inch 30 Millimeter
Outside Diameter	6.299 Inch 160 Millimeter
Bore	3.543 Inch 90 Millimeter
bore diameter:	90 mm
static load capacity:	178000 N
outside diameter:	160 mm
precision rating:	ISO Class 0
overall width:	30 mm
maximum rpm:	5000 rpm
flanges:	(2) Outer Ring, (1) Inner Ring
bearing material:	Hardened Alloy Steel
bore type:	Straight
cage material:	High Strength Machined Brass Rivetless w/ square holes
number of rows:	1
finish/coating:	Uncoated
internal clearance:	CN
closure type:	Open
operating temperature range:	-40 to 120 °C

fillet radius:	2 mm
dynamic load capacity:	152000 N
manufacturer product page:	Click here