

NSK N1013RXZTPKR cylindrical roller bearings

Offer High Quality Brand NSK N1013RXZTPKR cylindrical roller bearings 15x35x13.8 Size (mm) .Contact Us 15 Bore Diameter (mm) Online to Get Best Quote.

| | |
|-----------------------------------|------------|
| Size (mm) | 15x35x13.8 |
| Bore Diameter (mm) | 15 |
| Outer Diameter (mm) | 35 |
| Width (mm) | 13,8 |
| D | 35 mm |
| d | 15 mm |
| C | 13.8 mm |
| B | 14 mm |
| D1 | 26 mm |
| F | 20 mm |
| r1,2 – min. | 0.6 mm |
| r3,4 – min. | 0.3 mm |
| Basic dynamic load rating – C | 7.5 kN |
| Basic static load rating – C0 | 9.3 kN |
| Fatigue load limit – Pu | 1.1 kN |
| Maximum dynamic radial loads – Fr | 9.5 kN |
| Maximum static radial loads – F0r | 13.7 kN |
| Limiting speed | 5000 r/min |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.081 |

| | |
|------------------------------|--|
| EAN | 7316577011930 |
| Product Group | B04144 |
| Roller Surface Profile | Crowned |
| Profile | Yoke Type |
| Enclosure | Sealed |
| Rolling Element | Needle Bearing |
| Relubricatable | Yes |
| Inch – Metric | Metric |
| Other Features | Caged With Inner Ring Lip Seal |
| Long Description | 15MM Bore; 35MM Roller Diameter; 13.8MM Roller Width; Crowned Roller; Yoke Type; Sealed; Needle Bear |
| UNSPSC | 31171530 |
| Harmonized Tariff Code | 8482.40.00.00 |
| Noun | Bearing |
| Keyword String | Cam Follower |
| Manufacturer Item Number | NA 2202.2RS |
| Weight / LBS | 0.165 |
| Roller Diameter | 1.378 Inch 35 Millimeter |
| Roller Width | 0.543 Inch 13.8 Millimeter |
| Bore | 0.591 Inch 15 Millimeter |
| roller diameter: | 35 mm |
| radial static load capacity: | 13.7 kN |
| roller width: | 13.8 mm |
| roller material: | Chrome Steel |

| | |
|-------------------------------------|-------------------------|
| bore diameter: | 15 mm |
| maximum rpm: | 5000 RPM |
| roller shape: | Crowned |
| lubrication hole location: | Inner Ring |
| bearing element: | Needle Rollers |
| axial dynamic load capacity: | 7.21 kN |
| closure type: | Sealed |
| axial static load capacity: | 9 kN |
| operating temperature range: | Maximum of +280 °F |
| finish/coating: | Uncoated |
| radial dynamic load capacity: | 9.65 kN |
| standards met: | ANSI/ABMA Standard 18.1 |
| r1,2 min. | 0.6 mm |
| r3,4 min. | 0.3 mm |
| Basic dynamic load rating C | 7.48 kN |
| Basic static load rating C0 | 9.3 kN |
| Fatigue load limit Pu | 1.12 kN |
| Maximum dynamic radial load Fr max. | 9.5 kN |
| Maximum static radial load F0r max. | 13.7 kN |
| Mass support roller | 0.075 kg |