

NSK NAFW507840 needle roller bearings

NSK NAFW507840 needle roller bearings Needs Analysis , Manufacturing Service . 55x90x27.3 Size (mm) Get 90 Outer Diameter (mm) Your Free.

Size (mm)	55x90x27.3
Bore Diameter (mm)	55
Outer Diameter (mm)	90
Width (mm)	27,3
d	55 mm
D	90 mm
T	27,3 mm
d1	90 mm
r min.	1 mm
A	35 mm
D1	57 mm
R	72 mm
da min.	76 mm
Da max.	69 mm
ra max.	1 mm
Weight	0,656 Kg
Basic dynamic load rating (C)	70 kN
Basic static load rating (C0)	159 kN
(Grease) Lubrication Speed	2200 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A

Weight / Kilogram	0.77
EAN	0029176029561
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	Non-Precision
Component Description	Roller Assembly Plus Raceways
Other Features	Single Row With Aligning Seat
Long Description	55MM Bore 1; 57MM Bore 2; 90MM Outside Diameter; 27MM Height; Ball Bearing; Single Direction; Not Ba
Inch – Metric	Metric
UNSPSC	31171552
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer Item Number	53211
Weight / LBS	1.44623
Outside Diameter	3.543 Inch 90 Millimeter
Bore 2	2.244 Inch 57 Millimeter
Height	1.063 Inch 27 Millimeter
Bore 1	2.165 Inch 55 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
bore diameter:	55 mm

static load capacity:	35500 lbf
outside diameter:	90 mm
dynamic load capacity:	15700 lbf
overall width:	30 mm
operating temperature range:	Maximum of +120 °C
thrust bearing type:	Single-Direction
maximum rpm:	3200 rpm
outside diameter design:	Straight
cage material:	Steel Cage
separable or banded:	Separable
fillet radius:	1 mm
race type:	Flat
series:	52300
precision rating:	ABEC1, P0
SRI	6.85
hidYobi	53211
LangID	1
D_	90
SREX	0.05
C	70
B_	27.3
hidTable	ecat_NSSDTB
Oil rpm	3200
SRE	6.85
mass	0.656
GRS rpm	2200
ra	1
SRIX	0.05
D_a	69

SRIN	0
C0	159
SREN	0
D_1	57
Prod_Type3	TB_SD_WAS
da	76
DA_	12.7
Z_	16
yobi	53211
A_	35
T3	27.3
SDM_	72.5
r	1
KBRG	5121
R_	72