

NSK NCF2922V cylindrical roller bearings

NSK NCF2922V cylindrical roller bearings Deal is your source 184.15 mm da for OEM and accessories. We sell Genuine at discount prices.

da	184.15 mm
Da	359.999 mm
Ca	107.798 mm
A1	203.2 mm
A2	358.775 mm
S	4.763 mm
ba	83.344 mm
H	422.275 mm
H1	209.55 mm
H2	85.725 mm
J min.	571.5 mm
J max.	635 mm
J1	127 mm
L	749.3 mm
N1	34.925 mm
R1	122.237 mm
R2	42.862 mm
RG	1 NPT
PG	1/4 NPT
h	62.706 mm
Housing	SAF 540
Bearing	22240 CCK/W33

Adapter sleeve assembly	SNW 40×7.1/4
Stabilizing ring	SR-40-34
Taconite seal	TER 160
End plug (suffix Y)	EPR 21
Max. speed for Taconite seal	425 r/min
P60°	364 kN
P90°	218 kN
P120°	136 kN
P150°	120 kN
P180°	145 kN
Pa	58.7 kN
Mass pillow block	195 kg
Cap bolt	4 x 7/8-9 UNC
Cap bolt recommended tightening torque	271.2 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.25 in
Initial grease fill	2154.6 g