

NSK NN3921MBKR cylindrical roller bearings

Various types and sizes 0.0 Inventory N/A Minimum Buy Quantity to accommodate your NSK NN3921MBKR cylindrical roller bearings requirements.

| | |
|---------------------------|---|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 4.486 |
| EAN | 7316577057518 |
| Product Group | M06288 |
| Number of Mounting Holes | 2 |
| Mounting Method | Stepped Sleeve |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Spherical Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 5/8 Inch |
| Relubricatable | Yes |
| Insert Part Number | 22210 |
| Seals | Trigard |
| Housing Configuration | 1 Piece Solid |
| Inch – Metric | Inch |
| Other Features | Double Row Heavy Duty Locating Bearing Open End With Grub Screw |

| | |
|-------------------------------|--|
| Long Description | 2 Bolt Pillow Block; 1-15/16" Bore; 2-1/4" Base to Center Height; Stepped Sleeve Mount; Sp |
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | SYE 1.15/16 NH |
| Weight / LBS | 10.5 |
| Bolt Spacing Minimum | 6.75 Inch 171.45Millimeter |
| d | 1.938 Inch 49.225 Millimeter |
| B | 2.25 Inch 57.15 Millimeter |
| Actual Bolt Center to Center | 0 Inch 0Millimeter |
| Nominal Bolt Center to Center | 6.6 Inch 167 Millimeter |
| Bolt Spacing Maximum | 7.25 Inch 184.15Millimeter |
| D | 2.343 Inch 59.5 Millimeter |
| bore diameter: | 1.9375 in |
| bolt center-to-center length: | 7 in |
| overall length: | 8.8750 in |
| base width: | 2-1/2 in |
| overall height: | 4.5000 in |
| expansion type: | Non-Expansion Bearing (Fixed) |
| mounting: | Two-Bolt Base |
| finish/coating: | Uncoated |
| bearing type: | Spherical Roller |
| seal type: | Tri-Guard |
| bore type: | Round |
| radial dynamic load capacity: | 21600 lbf |
| housing construction: | Solid Pillow Block |

| | |
|------------------------------|---------------------|
| radial static load capacity: | 22400 lbf |
| base to bore centerline: | 2.5000 in |
| maximum rpm: | 2150 RPM |
| duty type: | Standard Duty |
| lubrication type: | Lubrication Fitting |
| housing material: | Cast Iron |
| series: | SYE |
| locking device: | Concentric Collar |
| replacement bearing: | 22210 |