

# NSK NNCF4880V cylindrical roller bearings

Shop NSK NNCF4880V cylindrical roller bearings huge online discount inventory. and Import machinery parts your 14 mm B car needs with Free Shipping and Free Extended 35 mm d Warranty.

d	35 mm
D	62 mm
B	14 mm
rs min	1 mm
Radial clearance class	C3
Mass	0.16 kg
Dynamic load, C	16 kN
Static load, C0	10.3 kN
Fatigue limit load, Cu	0.47 kN
f0	14.8
Nlim (grease)	6,800 rpm
Min operating temperature, Tmin	-25 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.95 Hz
Characteristic outer ring frequency, BPF0	4.6 Hz
Characteristic inner ring frequency, BRFI	6.4 Hz
da min	40 mm
da max	42 mm
Da max	57 mm

ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.16
EAN	3413520210571
Product Group	B00308
Enclosure	1 Seal
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	35MM Bore; 62MM Outside Diameter; 14MM Outer Race Diameter; 1 Seal; Ball Bearing; ABEC 1   ISO P0; N
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6007LUC3
Weight / LBS	0.342
Outer Race Width	0.551 Inch   14 Millimeter

Outside Diameter	2.441 Inch   62 Millimeter
Bore	1.378 Inch   35 Millimeter
bore diameter:	35 mm
static load capacity:	10300 N
outside diameter:	62 mm
precision rating:	ISO Class 0
overall width:	14 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Single Seal
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	14 mm
snap ring included:	Without Snap Ring
outer ring width:	14 mm
internal clearance:	C3
maximum rpm (grease):	6800 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	1 mm
dynamic load capacity:	16000 N
manufacturer product page:	<a href="#">Click here</a>