

NSK NNCF5030V cylindrical roller bearings

offers a NSK NNCF5030V cylindrical roller bearings selection of Genuine at Wholesale Prices. We 104.775 mm da are a NSK NNCF5030V cylindrical roller bearings Certified Parts Retailer

da	104.775 mm
Da	180 mm
Ca	55.804 mm
A1	111.125 mm
A2	155.575 mm
ba	46.831 mm
H	222.25 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
J1	60.325 mm
L	387.35 mm
N1	26.988 mm
R1	65.088 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	40.481 mm
Housing	SAFS 024 KA
Bearing	23024 CCK/W33
Adapter sleeve assembly	SNW 3024×4.1/8

Stabilizing ring	2 x 38151-24
Labyrinth ring	2 x LOR 112
PosiTrac Plus contact element	2 x B10724-113
End plug (suffix Y)	EPR 14
Max. speed for PosiTrac Plus seal	1350 r/min
P60°	141 kN
P90°	84.5 kN
P120°	52.5 kN
P150°	48 kN
P180°	57.4 kN
Pa	16.7 kN
Mass pillow block	39 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.875 in
Initial grease fill	181.44 g