

NSK RLM202820 needle roller bearings

Enjoy High Margins on Competitive Pricing.Great Wholesale Products 200 mm da 222.25 mm db at Low Costs.

da	200 mm
db	222.25 mm
dc	193.675 mm
Da	359.999 mm
Ca	137.82 mm
A1	203.2 mm
A2	374.65 mm
S	4.763 mm
ba	98.425 mm
H	422.275 mm
H1	209.55 mm
H2	85.725 mm
J min.	571.5 mm
J max.	635 mm
J1	127 mm
L	749.3 mm
N1	34.925 mm
R1	122.237 mm
R2	46.038 mm
RG	1 NPT
PG	1/4 NPT
h	63.5 mm
Housing	SAW 240

Bearing	23240 CC/W33
Lock nut	AN 40
Lock washer	W 40
Stabilizing ring	SR-40-34
Taconite seal (db shaft position)	TER 175
Taconite seal (dc shaft position)	TER 164
End plug (suffix Y)	EPR 22
Max. speed for Taconite seal	350 r/min
P60°	364 kN
P90°	218 kN
P120°	136 kN
P150°	120 kN
P180°	145 kN
Pa	77 kN
Mass pillow block	195 kg
Cap bolt	4 x 7/8-9 UNC
Cap bolt recommended tightening torque	271.2 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.25 in
Initial grease fill	2154.6 g