

# NSK RNAFW405034 needle roller bearings

Advance NSK RNAFW405034 needle roller bearings is your source for quality and accessories. shop online for 0.0 Inventory home delivery or pick up in TIMKEN Manufacturer Name one of our 10000 .

|                           |                          |
|---------------------------|--------------------------|
| Inventory                 | 0.0                      |
| Manufacturer Name         | TIMKEN                   |
| Minimum Buy Quantity      | N/A                      |
| Weight                    | 6.356                    |
| EAN                       | 0883450096942            |
| Product Group             | M06288                   |
| Number of Mounting Holes  | 2                        |
| Mounting Method           | V Lock                   |
| Housing Style             | 2 Bolt Pillow Block      |
| Rolling Element           | Spherical Roller Bearing |
| Housing Material          | Cast Steel               |
| Expansion / Non-expansion | Non-expansion            |
| Mounting Bolts            | 5/8 Inch                 |
| Relubricatable            | Yes                      |
| Insert Part Number        | 22212                    |
| Seals                     | Triple Lip Viton         |
| Housing Configuration     | 1 Piece Solid            |
| Inch – Metric             | Inch                     |
| Other Features            | Double Row   Double Nut  |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 2-1/4" Bore; 2-1/2" Base to Center Height; V Lock Mount; Spherical Ro |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Weight / LBS                  | 17   |
| D                             | 4.02 Inch   102.108 Millimeter   |
| Nominal Bolt Center to Center | 6.8 Inch   171.5 Millimeter  |
| Bolt Spacing Maximum          | 7.06 Inch   179.324Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| Bolt Spacing Minimum          | 6.5 Inch   165.1Millimeter   |
| d                             | 2.25 Inch   57.15 Millimeter   |
| B                             | 2.5 Inch   63.5 Millimeter   |