

# NSK RS-4824E4 cylindrical roller bearings

What is the best 13x6x5 Size (mm) place to buy 6 Outer Diameter (mm) NSK RS-4824E4 cylindrical roller bearings online? Manufacturing Service .

Size (mm)	13x6x5
Bore Diameter (mm)	13
Outer Diameter (mm)	6
Width (mm)	5
d	6 mm
D	13 mm
B	5 mm
d2	7.4 mm
D2	11.7 mm
r1,2 – min.	0.15 mm
da – min.	6.8 mm
da – max.	7.2 mm
Da – max.	12.2 mm
ra – max.	0.1 mm
Basic dynamic load rating – C	0.88 kN
Basic static load rating – C0	0.35 kN
Fatigue load limit – Pu	0.015 kN
Reference speed	110000 r/min
Limiting speed	53000 r/min
Calculation factor – kr	0.015
Calculation factor – f0	11
Inventory	0.0

Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.005
EAN	7316577746009
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	6MM Bore; 13MM Outside Diameter; 5MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	628/6-2Z
Weight / LBS	0.01
Outside Diameter	0.512 Inch   13 Millimeter
Outer Race Width	0.197 Inch   5 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Bore	0.236 Inch   6 Millimeter
bore diameter:	6 mm

static load capacity:	0.35 kN
outside diameter:	13 mm
precision rating:	Not Rated
overall width:	5 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
outer ring width:	5 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.1 mm
internal clearance:	C0
maximum rpm:	53000 RPM
dynamic load capacity:	0.88 kN
series:	62
d2 ≈	7.4 mm
D2 ≈	11.7 mm
r1,2 min.	0.15 mm
da min.	6.8 mm
da max.	7.2 mm
Da max.	12.2 mm
ra max.	0.1 mm
Basic dynamic load rating C	0.88 kN
Basic static load rating C0	0.35 kN
Fatigue load limit Pu	0.015 kN
Calculation factor kr	0.015
Calculation factor f0	7
Mass bearing	0.0026 kg