

# NSK RS-5008 cylindrical roller bearings

NSK RS-5008 cylindrical roller bearings 80x140x26 Size (mm) Warehouse offers 140 Outer Diameter (mm) car parts and car accessories. We sell discount online as well as cheap 80 Bore Diameter (mm) machinery parts.

Size (mm)	80x140x26
Bore Diameter (mm)	80
Outer Diameter (mm)	140
Width (mm)	26
d	80 mm
D	140 mm
B	26 mm
C	26 mm
r min.	2 mm
da min.	89 mm
da max	95,5 mm
Da max.	131 mm
ra max.	2 mm
Weight	1,4 Kg
Basic dynamic load rating (C)	72,5 kN
Basic static load rating (C0)	53 kN
(Grease) Lubrication Speed	4 500 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0

EAN	4547359005028
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	80MM Bore; 140MM Outside Diameter; 26MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No
Other Features	Deep Groove   Non-Friction Nitrile Rubber Seal   Shell Alvania Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	3.13056
Bore	3.15 Inch   80 Millimeter
Outside Diameter	5.512 Inch   140 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	1.024 Inch   26 Millimeter
bore diameter:	80 mm
static load capacity:	53000 N

outside diameter:	140 mm
precision rating:	ISO Class 0
overall width:	26 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	26 mm
snap ring included:	Without Snap Ring
outer ring width:	26 mm
internal clearance:	CN
maximum rpm (grease):	4500 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	2 mm
dynamic load capacity:	72500 N
manufacturer product page:	<a href="#">Click here</a>