

NSK STF820RV11110g cylindrical roller bearings

What is NSK STF820RV11110g cylindrical roller bearings 60x85x13 Size (mm) in mechanical engineering? Manufacturing Service . Upload your CAD file for an 85 Outer Diameter (mm) instant.

Size (mm)	60x85x13
Bore Diameter (mm)	60
Outer Diameter (mm)	85
Width (mm)	13
d	60 mm
D	85 mm
B	13 mm
C	13 mm
rn	0,5 mm
r min.	1 mm
da min.	65 mm
da max	66,5 mm
Da max.	80 mm
ra max.	1 mm
Weight	0,193 Kg
Basic dynamic load rating (C)	16,4 kN
Basic static load rating (C0)	14,3 kN
(Grease) Lubrication Speed	7 600 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A

Weight / Kilogram	0.191
EAN	4547359006940
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	60MM Bore; 85MM Outside Diameter; 13MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6912ZZ/2AS
Weight / LBS	0.422
Outside Diameter	3.346 Inch 85 Millimeter
Bore	2.362 Inch 60 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
Other Features	Deep Groove Shell Alvania Prelubricated
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	60 mm
precision rating:	ISO Class 0

outside diameter:	85 mm
finish/coating:	Uncoated
overall width:	13 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	13 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	13 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	7600 rpm
internal clearance:	CN
fillet radius:	1 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	8900 RPM
dynamic load capacity:	16400 N
series:	69
static load capacity:	14300 N
manufacturer product page:	Click here