

NTN 2211SK self aligning ball bearings

Request A Quote For 82.55×133.35×33.338 Size (mm) Your Special NTN 2211SK self aligning ball bearings 133,35 Outer Diameter (mm) Needs Today! Free Quotes. ISO 9001 certified.

| | |
|-------------------------------|---------------------|
| Size (mm) | 82.55×133.35×33.338 |
| Bore Diameter (mm) | 82,55 |
| Outer Diameter (mm) | 133,35 |
| Width (mm) | 33,338 |
| d | 82,55 mm |
| D | 133,35 mm |
| T | 33,338 mm |
| B | 33,338 mm |
| C | 26,195 mm |
| ra1 max. | 3,3 mm |
| a | 29 mm |
| r min. | 3,5 mm |
| r1 min. | 3,3 mm |
| Da | 119 mm |
| db | 90 mm |
| ra max. | 3,5 mm |
| da | 97 mm |
| Db | 128 mm |
| Weight | 1,757 Kg |
| Basic dynamic load rating (C) | 154 kN |
| Basic static load rating (C0) | 237 kN |
| (Grease) Lubrication Speed | 2600 r/min |

| | |
|-------------------------|-------------|
| (Oil) Lubrication Speed | 3600 r/min |
| Calculation factor (e) | 0,4 |
| Calculation factor (Y0) | 0,82 |
| LangID | 1 |
| ALP23 | 0 |
| outer r | 3.3 |
| ALP22 | 8 |
| D_ | 133.35 |
| ALP21 | 30 |
| SHOG_yobi | 47686/47620 |
| RAr | 240.456 |
| inner r | 3.5 |
| GRS rpm | 2600 |
| D_b | 128 |
| D_a | 119 |
| DE_ | 118.884 |
| SLR | 24 |
| Prod_Type3 | TRBSR_ID_A |
| BETA_ | 1 |
| ALPHA_ | 15.083 |
| SDM_ | 107.583 |
| DA1 | 11.889 |
| DA2 | 10.706 |
| hidYobi | 47686/47620 |
| Y1 | 1.5 |
| B_ | 33.338 |
| Oil rpm | 3600 |
| hidTable | ecat_NSTPRI |
| Y0 | 0.82 |

| | |
|----------|-------------|
| inner ra | 3.5 |
| outer rb | 3.3 |
| C0 | 237 |
| CUP | 0.577 |
| e | 0.4 |
| DA_ | 11.627 |
| BET21 | 2 |
| BET22 | 50 |
| BET23 | 0 |
| Z_ | 23 |
| C_ | 26.195 |
| yobi | 47686/47620 |
| KBRG | 3161 |
| CONE | 1.18 |
| DI_ | 96.176 |