

# NTN

## 2N2-6303EX3X9T2XLLVACM/L417QT S deep groove ball bearings

Online 50x90x19.8 Size (mm) NTN 2N2-6303EX3X9T2XLLVACM/L417QTS deep groove ball bearings Expert. More Choices. 90 Outer Diameter (mm) NTN 2N2-6303EX3X9T2XLLVACM/L417QTS deep groove ball bearings in Stock & Ready 50 Bore Diameter (mm) to Ship Now!

|                                   |            |
|-----------------------------------|------------|
| Size (mm)                         | 50x90x19.8 |
| Bore Diameter (mm)                | 50         |
| Outer Diameter (mm)               | 90         |
| Width (mm)                        | 19,8       |
| D                                 | 90 mm      |
| d                                 | 50 mm      |
| C                                 | 19.8 mm    |
| B                                 | 20 mm      |
| E                                 | 68 mm      |
| F                                 | 60 mm      |
| r1,2 – min.                       | 1 mm       |
| r3,4 – min.                       | 1 mm       |
| Basic dynamic load rating – C     | 26 kN      |
| Basic static load rating – C0     | 45.5 kN    |
| Fatigue load limit – Pu           | 5.7 kN     |
| Maximum dynamic radial loads – Fr | 34.5 kN    |
| Maximum static radial loads – F0r | 50 kN      |
| Limiting speed                    | 1600 r/min |
| r1,2 min.                         | 1 mm       |

|   |         |
|---|---------|
| r <sub>3,4</sub> min.                           | 1 mm    |
| Basic dynamic load rating C                     | 26 kN   |
| Basic static load rating C <sub>0</sub>         | 45.5 kN |
| Fatigue load limit P <sub>u</sub>               | 5.7 kN  |
| Maximum dynamic radial load F <sub>r</sub> max. | 34.5 kN |
| Maximum static radial load F <sub>0r</sub> max. | 50 kN   |
| Mass support roller                             | 0.62 kg |