

NTN 2P9002K thrust roller bearings

Find the discount NTN 2P9002K thrust roller bearings online you need . We 130 Outer Diameter (mm) offer ... If you check out our large selection 225x130x58 Size (mm) of NTN 2P9002K thrust roller bearings once .

Size (mm)	225x130x58
Bore Diameter (mm)	225
Outer Diameter (mm)	130
Width (mm)	58
d	130 mm
D	225 mm
H	58 mm
d1	203 mm
D1	166 mm
B	36.7 mm
B1	50.6 mm
C	30.1 mm
s	75.6 mm
r1,2 – min.	2.1 mm
da – min.	175 mm
db1 – max.	138 mm
db2 – max.	143 mm
Da – max.	194 mm
ra – max.	2 mm
Basic dynamic load rating – C	865 kN
Basic static load rating – C0	2500 kN

Fatigue load limit – Pu	280 kN
Reference speed	1600 r/min
Limiting speed	2600 r/min
Factor min. axial load – A	0.59
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	9.01
EAN	7316576608940
Product Group	B04311
Rolling Element	Spherical Roller Bearing
Self Aligning	Yes
Component Description	Roller Assembly plus Raceways
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Other Features	Single Row Window Type Cage
Long Description	130MM Bore 1; 165.5MM Bore 2; 225MM Outside Diameter; 58MM Height; Spherical Roller Bearing; Single
Inch – Metric	Metric
UNSPSC	31171507
Harmonized Tariff Code	8482.30.00.40
Noun	Bearing
Keyword 3	Spherical

Keyword String	Thrust Roller Spherical
Manufacturer Item Number	29326 E
Weight / LBS	19.842
Bore 2	6.516 Inch 165.5 Millimeter
Outside Diameter	8.858 Inch 225 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Bore 1	5.118 Inch 130 Millimeter
Height	2.283 Inch 58 Millimeter
bore diameter:	130 mm
operating temperature range:	Maximum of +392 °F
outside diameter:	225 mm
maximum rpm:	2600 RPM
overall width:	58 mm
separable type:	Non-Separable
cage material:	Steel
fillet radius:	2 mm
static load capacity:	2500 kN
series:	293
dynamic load capacity:	865 kN
d1 ≈	203 mm
D1 ≈	166 mm
r1,2 min.	2.1 mm
da min.	175 mm
db1 max.	138 mm
db2 max.	143 mm
Da max.	194 mm
ra max.	2 mm

Basic dynamic load rating C	865 kN
Basic static load rating C ₀	2500 kN
Fatigue load limit P _u	280 kN
Minimum axial load factor A	0.59
Mass bearing	9 kg