

NTN 2RNU7605 cylindrical roller bearings

What 22 mm B is NTN 2RNU7605 cylindrical roller bearings in mechanical engineering? Manufacturing Service . Upload 120 mm d your CAD file for 165 mm D an instant.

d	120 mm
D	165 mm
B	22 mm
rs min	1.1 mm
Radial clearance class	CN
Mass	1.15 kg
Dynamic load, C	53 kN
Static load, C ₀	54 kN
Fatigue limit load, C _u	2.06 kN
f ₀	16.5
N _{lim} (grease)	2,400 rpm
Min operating temperature, T _{min}	-25 °C
Max operating temperature, T _{max}	110 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	10.47 Hz
Characteristic outer ring frequency, BPF ₀	8.15 Hz
Characteristic inner ring frequency, BPFI	9.85 Hz
da min	126.5 mm
Da max	158.5 mm

ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.245
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	120MM Bore; 165MM Outside Diameter; 22MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; N
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	2.54
Inner Race Width	0 Inch 0 Millimeter

Bore	4.724 Inch 120 Millimeter
Outside Diameter	6.496 Inch 165 Millimeter
Outer Race Width	0.866 Inch 22 Millimeter