

# NTN 30244DF tapered roller bearings

100% Authentic. NTN 30244DF tapered roller bearings Highest Quality. N/A Minimum Buy Quantity Certified 0.0 Inventory Supplier.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 8.626  |
| EAN                       | 0883450347655  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | V Lock   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 20 Millimeter  |
| Relubricatable            | Yes  |
| Insert Part Number        | 22214  |
| Seals                     | Teflon Labyrinth   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Metric   |
| Other Features            | Double Row   Single Nut  |
| Long Description          | 2 Bolt Pillow Block; 60MM Bore; 76.2MM Base to Center Height; V Lock Mount; Spherical Roller Bearing |

|                               |                              |
|-------------------------------|------------------------------|
| UNSPSC                        | 31171511                     |
| Harmonized Tariff Code        | 8483.20.40.80                |
| Noun                          | Bearing                      |
| Keyword String                | Pillow Block                 |
| Manufacturer Item Number      | QVPXT14V060ST                |
| Weight / LBS                  | 22                           |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter         |
| d                             | 2.362 Inch   60 Millimeter   |
| B                             | 3 Inch   76.2 Millimeter     |
| Nominal Bolt Center to Center | 8.4 Inch   213 Millimeter    |
| D                             | 3.189 Inch   81 Millimeter   |
| Bolt Spacing Minimum          | 7.661 Inch   194.6Millimeter |
| Bolt Spacing Maximum          | 9.173 Inch   233Millimeter   |