

# NTN 30318U tapered roller bearings

High Quality NTN 30318U tapered roller bearings. Competitive Pricing. Accept 15x28x7 Size (mm) Small Order. Easy and 28 Outer Diameter (mm) Fast Shipping.

Size (mm)	15x28x7
Bore Diameter (mm)	15
Outer Diameter (mm)	28
Width (mm)	7
d	15 mm
D	28 mm
B	7 mm
C	7 mm
a	1.3 mm
b	0.95 mm
f	0.85 mm
r min.	0.3 mm
r1 min.	0.3 mm
D1	26.7 mm
D2	30.8 mm
Weight	0.017 Kg
Basic dynamic load rating (C)	4,3 kN
Basic static load rating (C0)	2,25 kN
(Grease) Lubrication Speed	26000 r/min
Bore Type	Cylindrical Bore
Configuration	Single Row
Enclosure	Snap Ring Groove with Snap Ring

Bore Size	15 mm
Outside Diameter	28 mm
Width	7 mm
Fillet Radius/Chamfer	0.3 mm
r1	0.3 mm
Snap Ring Width	0.9 mm
Snap Ring Outside Diameter	30.8 mm
D1 (max)	26.7 mm
a (max)	1.3 mm
b (min)	1 mm
Dynamic Load Rating	4,300 N
Static Load Rating	2,250 N
Limiting Speed – Grease	26,000 rpm
Limiting Speed – Oil	31,000 rpm
Factor fo	14.3
Radial Clearance	0.003 to 0.018 mm
da (min)	17 mm
Da (max)	26 mm
Dx (min)	31.5 mm
ra (max)	0.3 mm
Cy (max)	1.8 mm