

NTN 32232U tapered roller bearings

What are the types of NTN 32232U tapered roller bearings 55x120x48 Size (mm) ? Manufacturing Service . Get 120 Outer Diameter (mm) Your Free, Instant price, design 55 Bore Diameter (mm) review.

Size (mm)	55x120x48
Bore Diameter (mm)	55
Outer Diameter (mm)	120
Width (mm)	48
d	55 mm
D	120 mm
H	48 mm
d1	120 mm
r1 min.	1,5 mm
r2 min.	1,5 mm
D1	57 mm
da min.	94 mm
Da max.	81 mm
ra max.	1.5 mm
Weight	2,55 Kg
Basic dynamic load rating (C)	195 kN
Basic static load rating (C0)	400 kN
Fatigue load limit (Pu)	14,6
Reference speed	1800 r/min
Limiting speed	2400 r/min
Inventory	0.0

Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.651
EAN	7316576678097
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Component Description	Roller Assembly Plus Raceways
Other Features	Single Row
Long Description	55MM Bore 1; 57MM Bore 2; 120MM Outside Diameter; 48MM Height; Ball Bearing; Single Direction; Not B
Inch – Metric	Metric
UNSPSC	31171507
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer Item Number	51411
Weight / LBS	5.839
Bore 1	2.165 Inch 55 Millimeter
Bore 2	2.244 Inch 57 Millimeter
Height	1.89 Inch 48 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Outside Diameter	4.724 Inch 120 Millimeter

bore diameter:	55 mm
static load capacity:	400 kN
outside diameter:	120 mm
dynamic load capacity:	195 kN
overall width:	48 mm
maximum rpm:	2400 RPM
thrust bearing type:	Single-Direction
cage material:	Steel
outside diameter design:	Straight
fillet radius:	1.5 mm
separable or banded:	Separable
series:	514
precision rating:	ABEC 1 (ISO Class Normal)
d1 ≈	120 mm
D1 ≈	57 mm
r1,2 min.	1.5 mm
Basic dynamic load rating C	195 kN
Basic static load rating C0	400 kN
Fatigue load limit Pu	14.6 kN
Minimum load factor A	0.79
Mass bearing (including seat washer where applicable)	2.55 kg