

NTN 323126 tapered roller bearings

100% Authentic. NTN 323126 tapered roller bearings 105x225x49 Size (mm) Highest Quality. Certified 225 Outer Diameter (mm) Supplier.

Size (mm)	105x225x49
Bore Diameter (mm)	105
Outer Diameter (mm)	225
Width (mm)	49
d	105 mm
D	225 mm
B	49 mm
C	49 mm
Angle (α)	30 °
a	23.1 mm
r min.	3 mm
r1 min.	1.1 mm
2B	98 mm
da min.	112 mm
Da max.	218 mm
ra max.	1 mm
Weight	9.34 Kg
Basic dynamic load rating (C)	355 kN
Basic static load rating (C0)	410 kN
(Grease) Lubrication Speed	2100 r/min
Bore Type	Cylindrical Bore
Enclosure	Open

Configuration	Duplex
Bore Size	105 mm
Outside Diameter	225 mm
Width	49 mm
Fillet Radius/Chamfer	3 mm
r1	1.1 mm
Dynamic Load Rating	355,000 N
Static Load Rating	410,000 N
Limiting Speed – Grease	2,100 rpm
Limiting Speed – Oil	2,800 rpm
da1 (min)	119 mm
da2 (min)	112 mm
Da1 (max)	211 mm
Da2 (max)	218 mm
ra (max)	2.5 mm
ra1 (max)	1 mm