

# NTN 32914X tapered roller bearings

NTN 32914X tapered roller bearings Industries and Applications ? We sell discount online as 153.797 mm Ca well as cheap machinery parts. 201.613 mm da

da	201.613 mm
Da	399.999 mm
Ca	153.797 mm
A1	222.25 mm
A2	368.3 mm
S	4.763 mm
ba	107.95 mm
H	474.663 mm
H1	241.3 mm
H2	95.25 mm
J min.	628.65 mm
J max.	708.025 mm
J1	133.35 mm
L	831.85 mm
N1	41.275 mm
R1	130.175 mm
R2	46.831 mm
RG	1 NPT
PG	1/4 NPT
h	80.963 mm
Housing	SAW 544
Bearing	23244 CCK/W33

Adapter sleeve assembly	SNW 144×7.15/16
Stabilizing ring	SR-44-38
Taconite seal	TER 167
End plug (suffix Y)	EPR 23
Max. speed for Taconite seal	385 r/min
P60°	423 kN
P90°	254 kN
P120°	160 kN
P150°	145 kN
P180°	173 kN
Pa	95.2 kN
Mass pillow block	284 kg
Cap bolt	4 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	2749.95 g