

NTN 413140 tapered roller bearings

NTN 413140 tapered roller bearings Engineering Calculator , Manufacturing Service . Get Your Free. 130x180x32 Size (mm)

| | |
|-------------------------------|------------|
| Size (mm) | 130x180x32 |
| Bore Diameter (mm) | 130 |
| Outer Diameter (mm) | 180 |
| Width (mm) | 32 |
| d | 130 mm |
| D | 180 mm |
| T | 32 mm |
| B | 32 mm |
| C | 25 mm |
| a | 31,4 mm |
| r min. | 2 mm |
| r1 min. | 1,5 mm |
| da min. | 142 mm |
| Da min | 168 mm |
| Da max. | 170 mm |
| db max. | 140 mm |
| Db min. | 173 mm |
| ra max. | 2 mm |
| rb max. | 1,5 mm |
| Weight | 2,46 Kg |
| Basic dynamic load rating (C) | 200 kN |
| Basic static load rating (C0) | 365 kN |
| (Grease) Lubrication Speed | 1800 r/min |

| | |
|-------------------------|------------|
| (Oil) Lubrication Speed | 2400 r/min |
| Calculation factor (e) | 0,34 |
| Calculation factor (Y0) | 0,97 |
| LangID | 1 |
| outer r | 1.5 |
| D_ | 180 |
| TC-BET22 | 50 |
| TC-BET21 | 1 |
| TC-BET23 | 0 |
| inner r | 2 |
| mass | 2.46 |
| GRS rpm | 1800 |
| D_b | 173 |
| Cr | 20400 |
| TC-RA | 390.5 |
| DE_ | 167.309 |
| T-ALP23 | 0 |
| db | 140 |
| T-ALP22 | 30 |
| Prod_Type3 | TRBSR_MD_A |
| da | 142 |
| T-ALP21 | 25 |
| Iso | 2CC |
| ALPHA_ | 12.75 |
| SDM_ | 155.392 |
| SBRG | 29 |
| D_a2 | 168 |
| hidYobi | HR32926J |
| Y1 | 1.8 |

| | |
|----------|-------------|
| D_a1 | 170 |
| B_ | 32 |
| hidTable | ecat_NSTPRM |
| Oil rpm | 2400 |
| C0r | 37500 |
| Y0 | 0.97 |
| TC-SLR | 23 |
| inner ra | 2 |
| outer rb | 1.5 |
| C0 | 365 |
| Sa | 6 |
| Sb | 7 |
| e | 0.34 |
| DA_ | 12.127 |
| Z_ | 35 |
| C_ | 25 |
| yobi | HR32926J |
| TC-DA1 | 12.494 |
| TC-DA2 | 11.76 |
| KBRG | 3111 |
| DI_ | 143.474 |