

NTN 430328XU tapered roller bearings

What is the best place 5 mm B to buy NTN 430328XU tapered roller bearings online? Manufacturing 5 mm d Service .

d	5 mm
D	16 mm
B	5 mm
rs min	0.3 mm
Radial clearance class	C3
Mass	0.005 kg
Dynamic load, C	1.76 kN
Static load, C0	0.68 kN
Fatigue limit load, Cu	0.03 kN
f0	12.4
Nlim (grease)	37,000 rpm
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
da min	7 mm
da max	7.6 mm
Da max	14 mm
ra max	0.3 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.005

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	5MM Bore; 16MM Outside Diameter; 5MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Fi
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Outer Race Width	0.197 Inch 5 Millimeter
Bore	0.197 Inch 5 Millimeter
Outside Diameter	0.63 Inch 16 Millimeter
Inner Race Width	0 Inch 0 Millimeter