

NTN 432322 tapered roller bearings

With over 10170 full-service stores, our NTN 432322 tapered roller bearings inventory 28 mm d is extensive and our 18 mm B parts are priced right. 68 mm D within 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

d	28 mm
D	68 mm
B	18 mm
a min	3.07 mm
a max	3.28 mm
Ca min	4.77 mm
Ca max	4.98 mm
rs min	1.1 mm
rNs min	0.5 mm
D3 max	64.82 mm
b min	1.9 mm
b max	2.2 mm
r0 max	0.6 mm
D4 max	74.6 mm
f	1.7 mm
Snap ring reference	R68
Radial clearance class	CN
Mass	0.28 kg
Dynamic load, C	26.7 kN
Static load, C0	14 kN

Fatigue limit load, C_u	0.64 kN
f_0	12.4
N_{lim} (grease)	7,400 rpm
Min operating temperature, T_{min}	-25 °C
Max operating temperature, T_{max}	110 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.52 Hz
Characteristic outer ring frequency, BPF0	2.57 Hz
Characteristic inner ring frequency, BRFI	4.43 Hz
$d_{a \min}$	34.5 mm
$d_{a \max}$	38.5 mm
$D_{a \max}$	61.5 mm
$r_{a \max}$	1 mm
$r_{Na \max}$	0.5 mm
$D_b \min$	76 mm