

NTN 4T-09074/09194 tapered roller bearings

LET OUR 120x165x29 Size (mm) NTN 4T-09074/09194 tapered roller bearings EXPERTS GET YOU 120 Bore Diameter (mm) THE 165 Outer Diameter (mm) PARTS YOU NEED.

Size (mm)	120x165x29
Bore Diameter (mm)	120
Outer Diameter (mm)	165
Width (mm)	29
d	120 mm
D	165 mm
T	29 mm
B	29 mm
C	23 mm
a	29,2 mm
r min.	1,5 mm
r1 min.	1,5 mm
da min.	131 mm
Da min	155 mm
Da max.	156 mm
db max.	129 mm
Db min.	160 mm
ra max.	1,5 mm
rb max.	1,5 mm
Weight	1,8 Kg
Basic dynamic load rating (C)	161 kN
Basic static load rating (C0)	291 kN

(Grease) Lubrication Speed	1900 r/min
(Oil) Lubrication Speed	2600 r/min
Calculation factor (e)	0,35
Calculation factor (Y0)	0,95
LangID	1
outer r	1.5
D_	165
TC-BET22	50
TC-BET21	1
TC-BET23	0
inner r	1.5
mass	1.8
GRS rpm	1900
D_b	160
Cr	16400
TC-RA	349.853
DE_	153.809
T-ALP23	0
db	129
T-ALP22	10
Prod_Type3	TRBSR_MD_A
da	131
T-ALP21	26
Iso	2CC
ALPHA_	13.083
SDM_	143.132
SBRG	29
D_a2	155
hidYobi	HR32924J

Y1	1.7
D_a1	156
B_	29
hidTable	ecat_NSTPRM
Oil rpm	2600
C0r	29700
Y0	0.95
TC-SLR	20.5
inner ra	1.5
outer rb	1.5
C0	291
Sa	6
Sb	6
e	0.35
DA_	10.867
Z_	35
C_	23
yobi	HR32924J
TC-DA1	11.194
TC-DA2	10.539
KBRG	3111
DI_	132.455