

# NTN 4T-1755/1729 tapered roller bearings

NTN 4T-1755/1729 tapered roller bearings, Units and Housings CAD models , Manufacturing N/A Minimum Buy Quantity Service 0.0 Inventory . Get Your Free.

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	0.458
Product Group	B04270
Enclosure	2 Seals
Precision Class	ABEC 5   ISO P5
Material – Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	0 Degree
Preload	None
Raceway Style	Not Applicable
Cage Material	Steel
Rolling Element	Ball Bearing
Enclosure Type	Non Contact Seal
Flush Ground	No
Inch – Metric	Metric
Other Features	Single Row   Deep Groove   C3 Clearance
Long Description	50MM Bore; 90MM Outside Diameter; 20MM Width; 2 Seals Enclosure; ABEC 5   ISO P5 Precision; Steel Ba

UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Deep Groove Ball
Manufacturer Item Number	6210M2LLBC3P5
Weight / LBS	1.01
D	3.543 Inch   90 Millimeter
d	1.969 Inch   50 Millimeter
B	0.787 Inch   20 Millimeter
bore diameter:	50 mm
static load capacity:	23200 N
outside diameter:	90 mm
precision rating:	ISO Class 5
overall width:	20 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	20 mm
snap ring included:	Without Snap Ring
outer ring width:	20 mm
internal clearance:	C3
maximum rpm (grease):	7100 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	1.1 mm
dynamic load capacity:	35000 N
manufacturer product page:	<a href="#">Click here</a>