

# NTN 4T-33262/33462 tapered roller bearings

170 Million used NTN 4T-33262/33462 tapered roller bearings instantly 33014M Series searchable. Shop our large selection of parts based on brand, price, description, and location. Order the with stock X33014M Cone Part Number ... METRIC Design Units

Series	33014M
Cone Part Number	X33014M
Design Units	METRIC
Cage Type	Stamped Steel
C1 – Dynamic Radial Rating (Two-Row, 1 million revolutions) <sup>1</sup>	60000 lbf
C90(2) – Dynamic Radial Rating (Two-Row, 90 million revolutions) <sup>2</sup>	15600 lbf
d	70 mm
B – Cone Width	31.000 mm
WPD	104.5 mm
DD	95.3 mm
R – Cone Backface To Clear Radius <sup>3</sup>	1.520 mm
da – Cone Frontface Backing Diameter	77 mm
db – Cone Backface Backing Diameter	79 mm
Ab – Cage-Cone Frontface Clearance	3.6 mm
Aa – Cage-Cone Backface Clearance	1 mm
a – Effective Center Location <sup>4</sup>	-8.6 mm
C90 – Dynamic Radial Rating (90 million revolutions) <sup>5</sup>	39800 N

C1 – Dynamic Radial Rating (1 million revolutions) <sup>6</sup>	153000 N
C0 – Static Radial Rating	236000 N
Ca90 – Dynamic Thrust Rating (90 million revolutions) <sup>7</sup>	19400 N
K – Factor <sup>8</sup>	2.05
G1 – Heat Generation Factor (Roller-Raceway)	105.3
G2 – Heat Generation Factor (Rib-Roller End)	50.1
Cg – Geometry Factor	0.0985