

NTN 4T-33889/33821 tapered roller bearings

What are the types of NTN 4T-33889/33821 tapered roller bearings 198.438 mm da ? 101.803 mm Ca Manufacturing Service . Get Your Free, Instant price, design review.

da	198.438 mm
Da	339.999 mm
Ca	101.803 mm
A1	190.5 mm
A2	273.05 mm
ba	80.169 mm
H	401.637 mm
H1	200.025 mm
H2	79.375 mm
J min.	549.275 mm
J max.	619.125 mm
J1	114.3 mm
L	711.2 mm
N1	34.925 mm
R1	120.65 mm
R2	42.069 mm
RG	1 NPT
PG	1/4 NPT
h	57.15 mm
Housing	SAF 044 KA
Bearing	23044 CCK/W33
Adapter sleeve assembly	SNW 3044×7.13/16

Stabilizing ring	2 x 36053-140
Labyrinth ring	2 x LOR 165
PosiTrac Plus contact element	2 x B10724-167
End plug (suffix Y)	EPR 23
Max. speed for PosiTrac Plus seal	725 r/min
P60°	290 kN
P90°	173 kN
P120°	107 kN
P150°	94.3 kN
P180°	113 kN
Pa	59.6 kN
Mass pillow block	153 kg
Cap bolt	4 x 7/8-9 UNC
Cap bolt recommended tightening torque	271.2 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.25 in
Initial grease fill	1672.65 g