

# NTN 4T-418/414 tapered roller bearings

Enjoy 0.0 Inventory N/A Minimum Buy Quantity High Margins on Competitive Pricing.Great Wholesale SKF Manufacturer Name Products at Low Costs.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | SKF  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 66.009   |
| EAN                       | 7316576602795  |
| Product Group             | B04311   |
| Internal Clearance        | C3-Loose   |
| Mounting Method           | Adapter Mount  |
| Rolling Element           | Spherical Roller Bearing   |
| Bore Profile              | Tapered  |
| Cage Material             | Steel  |
| Enclosure                 | Open   |
| Number of Rows of Rollers | Double Row   |
| Relubricatable            | Yes  |
| Withdrawal Sleeve         | AH3148 A0H3148 (Specify bore)  |
| Withdrawal Nut            | HM52T  |
| Inch – Metric             | Metric   |
| Long Description          | 240MM Tapered Bore; 400MM Outside Diameter; 128MM Width; C3-Loose Clearance; Adapter Mount; Double R |

|                              |   |
|------------------------------|---|
| Other Features               | Order adapter or withdrawal sleeve or nut separately. Others may be available |
| UNSPSC                       | 31171510  |
| Harmonized Tariff Code       | 84823080  |
| Noun                         | Bearing   |
| Keyword String               | Spherical   |
| Weight / LBS                 | 145.395   |
| B                            | 5.039 Inch   128 Millimeter   |
| d                            | 9.449 Inch   240 Millimeter   |
| Adapter Part Number          | SNP3148 H3148 (Specify bore) Inch   H3148 (Specify bore) Millimeter           |
| D                            | 15.748 Inch   400 Millimeter  |
| bore diameter:               | 240 mm  |
| maximum rpm:                 | 1600 RPM  |
| outside diameter:            | 400 mm  |
| operating temperature range: | Maximum of +390 °F  |
| overall width:               | 128 mm  |
| cage material:               | Steel   |
| bore type:                   | Tapered 1:12  |
| bearing material:            | Steel   |
| outer ring type:             | Not Split   |
| cage type:                   | Inner Ring Guided   |
| internal clearance:          | C3  |
| precision rating:            | Not Rated   |
| closure type:                | Open  |
| finish/coating:              | Uncoated  |
| lubrication hole type:       | Lubrication Groove & Hole   |
| outer ring width:            | 128 mm  |

|                        |         |
|------------------------|---------|
| dynamic load capacity: | 2080 kN |
| fillet radius:         | 3 mm    |
| static load capacity:  | 3200 kN |
| series:                | 231     |