

NTN 4T-498/492A tapered roller bearings

YOU'LL FIND AN 72 Bore Diameter (mm) EXTENSIVE SELECTION OF NTN 4T-498/492A tapered roller bearings 72x30x27 Size (mm) FOR SALE.

Size (mm)	72x30x27
Bore Diameter (mm)	72
Outer Diameter (mm)	30
Width (mm)	27
d	30 mm
D	72 mm
B	27 mm
d1	43.9 mm
D1	58.1 mm
r1,2 – min.	1.1 mm
da – min.	37 mm
Da – max.	65 mm
ra – max.	1 mm
Basic dynamic load rating – C	41 kN
Basic static load rating – C0	30 kN
Fatigue load limit – Pu	1.3 kN
Reference speed	16000 r/min
Limiting speed	8500 r/min
Calculation factor minimum radial load – kr	0.06
Calculation factor – f0	13
Inventory	0.0

Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.513
EAN	7316577004581
Product Group	B00152
bore diameter:	30 mm
static load capacity:	30 kN
outside diameter:	72 mm
precision rating:	Not Rated
overall width:	27 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Fiberglass Reinforced Nylon
closure type:	Open
outer ring width:	27 mm
row type & fill slot:	Double Row Non-Fill Slot
fillet radius:	1 mm
internal clearance:	C0
maximum rpm:	8500 RPM
dynamic load capacity:	41 kN
series:	43
d1 ≈	43.9 mm
D1 ≈	58.1 mm
r1,2 min.	1.1 mm
da min.	37 mm
Da max.	65 mm
ra max.	1 mm

Basic dynamic load rating C	41 kN
Basic static load rating C ₀	30 kN
Fatigue load limit P _u	1.27 kN
Calculation factor k _r	0.06
Calculation factor f ₀	13.2
Mass bearing	0.5 kg