

NTN 4T-580/572D tapered roller bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all your NTN 4T-580/572D tapered roller bearings N/A Minimum Buy Quantity needs – including routine maintenance, major repairs, warranty service, and equipment inspections. 0.0 Inventory

| | |
|--------------------------|---------------|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| EAN | 0883450508988 |
| Weight / US pound | 0.01 |
| Product Group | M06110 |
| Shaft Size | 2.165 in |
| Shaft Size Type | Metric |
| Weight | 15.0 lb |
| UPC Code | 0883450508988 |
| Type E Open Cover Number | EUDR-2 3/16 |
| Dimension B | 3-3/4 in |
| Dimension L | 9-5/8 in |
| Dimension A | 2-5/8 in |
| Dimension J Min. | 7-5/8 in |
| Dimension J Max. | 7-7/8 in |
| Bolt Diameter | 5/8 in |
| Dimension N | 3/4 in |
| Dimension N1 | 7/8 in |
| Dimension H1 | 1-1/2 in |

| | |
|--|---|
| Dimension H2 | 5 in |
| Dimension d1 | 3-3/4 in |
| Dimension H | 2-1/2 in |
| Dimension Ac | 4.975 in |
| Dimension d2 | 4.7 in |
| e | 0.36 |
| X (if $F_a/F_r \leq e$) | 0.87 |
| Y (if $F_a/F_r \leq e$) | 2.38 |
| X (if $F_a/F_r > e$) | 0.7 |
| Y (if $F_a/F_r > e$) | 2.87 |
| K Factor | 1.65 |
| C90 Dynamic Load Rating ¹ | 10900 lb |
| C0 Static Load Rating | 48200 lb |
| Fa-max Maximum Permissible Thrust Load ² | 3454 lb |
| Fr-max Maximum Allowable Slip Fit Radial Load ³ | 8900 lb |
| Max. Speed ⁴ | 2730 rpm |
| Note | Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to |