

# NTN 4T-595/592A tapered roller bearings

With over 10170 full-service stores, our NTN 4T-595/592A tapered roller bearings inventory is extensive and our parts are priced right. within 24 30 Bore Diameter (mm) hours. This helps you maximize your productivity by saving time and your 30x72x30.2 Size (mm) hard-earned dollars.

Size (mm)	30x72x30.2
Bore Diameter (mm)	30
Outer Diameter (mm)	72
Width (mm)	30.2
d	30 mm
D	72 mm
B	30.2 mm
C	30.2 mm
a	36.2 mm
r min.	1.1 mm
da min.	37 mm
da max	41.3 mm
Da max.	65 mm
ra max.	1 mm
Weight	0.510 Kg
Basic dynamic load rating (C)	34.3 kN
Basic static load rating (C0)	25.2 kN
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A

Weight / Kilogram	0.625
EAN	0605790370298
Product Group	B00152
Enclosure	2 Metal Shields
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	24 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	30MM Bore; 72MM Outside Diameter; 30.2MM Width; 2 Metal Shields; No Flush Ground; Ball Bearing; Doub
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Bore	1.181 Inch   30 Millimeter
Outside Diameter	2.835 Inch   72 Millimeter
Width	1.189 Inch   30.2 Millimeter