

NTN 4T-65237/65500 tapered roller bearings

How do I place an EMERGENCY order for a NTN 4T-65237/65500 tapered roller bearings 42,862 Bore Diameter (mm) that I want to pick up at a our store?

Bore Diameter (mm)	42,862
d	42,862 mm
s1	30.2 mm
A	48,3 mm
A1	32 mm
B	49,2 mm
G	12 mm
H	107 mm
H1	54 mm
H2	21 mm
J	143,7 mm
L	187 mm
N	22,7 mm
N1	14 mm
Weight	2,4 Kg
Basic dynamic load rating (C)	33,2 kN
Basic static load rating (C0)	21,6 kN
Fatigue load limit (Pu)	0,915
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.41

EAN	7316577758415
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	YAR 209-111-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch – Metric	Inch
Other Features	Single Row Standard Duty Wide Inner Race Y Bearing Has Flinger
Long Description	2 Bolt Pillow Block; 1-11/16" Bore; 2-1/8" Base to Center Height; Set Screw Mount; Ball Be
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SY 1.11/16 TF
Weight / LBS	5.3
Base to Center Height	2.125 Inch 53.98 Millimeter
Nominal Bolt Center to Center	5.8 Inch 146.5 Millimeter
Bore	1.688 Inch 42.875 Millimeter

Bolt Spacing Minimum	5.313 Inch 134.95Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
Bolt Spacing Maximum	6 Inch 152.4Millimeter
Length Thru Bore	1.938 Inch 49.225 Millimeter
Housing material	Cast iron
A5	26.5 mm
B4	8 mm
J max.	152 mm
J min.	135 mm
RG	1/4-28 UNF
R1	4 mm
Rα	45 °
DN	6.5 mm
SWN	7 mm
GN	1/4-28 SAE-LT
J6	173 mm
J7	17 mm
N4	4 mm
Basic dynamic load rating C	33.2 kN
Basic static load rating C0	21.6 kN
Fatigue load limit Pu	0.915 kN
Limiting speed	4300 r/min
Mass bearing unit	2.25 kg
Thread grub screw G2	5/16-24 UNF
Hexagonal key size for grub screw N	3.969 mm
Recommended tightening torque for grub screw	6.5 N·m
Recommended diameter for attachment bolts, mm G	12 mm

Recommended diameter for attachment bolts, inch G	0.5 in
Housing	SY 509 M
Bearing	YAR 209-111-2F
End cover	ECY 209